Universal Library of Medical and Health Sciences
Research Article

ISSN: 3064-6545 | Volume 4, Issue 2

Open Access | PP: 58-62

DOI: https://doi.org/10.70315/uloap.ulmhs.2026.0402006

Preventive Structural Preservation in E-File Manicure: Practical Application of the Zero-Base Safe Removal™ Method

Liudmyla Lysenok

Nail Technology / E-file Manicure / Preventive Nail Care. ORCID: https://orcid.org/0009-0008-2374-7242

Abstract

The rapid development of the global nail service industry has transformed manicure and pedicure procedures into highly technical professional practices requiring not only aesthetic precision but also a deep understanding of safety, structural preservation, and preventive methodology. Alongside the increasing popularity of e-file manicure systems and long-wear artificial coatings, the number of clients experiencing nail plate thinning, overfiling, thermal discomfort, and mechanical trauma has also increased significantly.

In many cases, damage to the natural nail plate is not caused by cosmetic products themselves but by uncontrolled abrasive interaction between mechanical tools and the biological structure of the nail. Excessive pressure, unstable hand positioning, chaotic drill bit movement, aggressive filing techniques, and complete removal "to zero" frequently lead to disruption of keratin structures and long-term weakening of the nail plate.

This article examines the concept of preventive structural preservation in e-file manicure through the practical application of the Zero-Base Safe Removal™ method — a proprietary technology of controlled material reduction designed to minimize traumatic mechanical impact during artificial material removal procedures.

The study explores the scientific rationale of the method, including biomechanics of the nail plate, mechanics of abrasive interaction, ergonomic stabilization principles, thermal load regulation, and vector-guided drill movement systems. Particular attention is given to the role of the residual protective layer as a mechanical buffer that reduces localized stress and prevents direct contact between the abrasive tool and the natural nail surface.

The article is based on long-term professional observations, practical implementation of preventive methodology in salon and independent nail service practice, and analysis of procedural safety standards within modern nail technology.

The findings suggest that preventive structural preservation approaches may significantly reduce the frequency of overfiling, improve long-term nail integrity, optimize workflow stability, and contribute to the formation of safer professional standards in modern nail care education and practice.

Keywords: *E-File Manicure, Preventive Nail Care, Structural Preservation, Overfiling Prevention, Nail Biomechanics, Nail Safety, Residual Protective Layer, Ergonomic Stabilization, Zero-Base Safe Removal™.*

INTRODUCTION

The modern nail service industry has undergone significant transformation over the last decade. Procedures that were previously considered primarily aesthetic now increasingly incorporate principles of preventive care, structural preservation, ergonomics, and procedural safety. The evolution of professional nail technology has created growing demand for techniques capable of balancing high aesthetic standards with preservation of the natural nail structure.

One of the most technically sensitive stages in nail procedures is the removal of artificial material. This stage directly influences the condition of the natural nail plate, the stability of subsequent coatings, and the long-term health of the client's nails. Despite technological advancements in products and equipment, aggressive removal techniques continue to remain widespread in professional practice.

Many conventional approaches prioritize complete removal of material, speed of execution, and visual cleaning of the nail surface. However, such techniques frequently involve excessive abrasive impact on the natural nail plate. As a

Citation: Liudmyla Lysenok, "Preventive Structural Preservation in E-File Manicure: Practical Application of the Zero-Base Safe Removal™ Method", Universal Library of Medical and Health Sciences, 2026; 4(2): 58-62. DOI: https://doi.org/10.70315/uloap.ulmhs.2026.0402006.

result, clients often experience thinning of the nail structure, increased sensitivity, mechanical discomfort, thermal trauma, and reduced durability of future coatings.

The increasing frequency of such complications has intensified discussions regarding safety standards in hardware manicure and e-file procedures. Modern professional practice increasingly recognizes that the quality of nail services should not be evaluated solely by visual appearance but also by the technician's ability to preserve the structural integrity of the natural nail.

Within this context, preventive methodologies have become increasingly important. Preventive approaches focus on minimizing mechanical trauma through controlled movement systems, ergonomic stabilization, proper pressure distribution, and preservation of functional nail architecture.

The Zero-Base Safe Removal™ method was developed as a response to the growing need for safer material removal systems within modern nail technology. The method introduces a fundamentally different approach to removal procedures by prioritizing controlled material reduction rather than complete aggressive elimination of the artificial coating.

A key innovation of the method is the introduction of a controlled residual protective layer that functions as a mechanical barrier between the drill bit and the natural nail plate. This principle significantly reduces the risk of direct abrasive trauma and creates conditions for long-term structural preservation.

The methodology also integrates:

- biomechanics of the nail plate;
- ergonomics of professional movement;
- vector-guided drill mechanics;
- thermal load control;
- stabilization systems for safe e-file operation.

Unlike traditional removal techniques that often treat the removal stage as a purely technical preparatory step, the Zero-Base Safe Removal™ system positions material removal as a critically important phase influencing long-term procedural outcomes and structural preservation of the natural nail.

This article examines the scientific rationale, practical application, preventive significance, and professional value of structural preservation principles within the framework of the Zero-Base Safe Removal™ method.

MATERIALS AND METHODS

The present article is based on long-term professional observations and practical application of preventive e-file manicure techniques in salon and independent nail service practice.

The observational analysis was conducted during practical work involving clients receiving:

- hardware manicure procedures;
- gel polish maintenance;
- artificial material correction;
- e-file removal procedures;
- structural nail correction services.

The practical implementation of the Zero-Base Safe Removal™ method was analyzed across various procedural conditions involving different levels of material thickness, nail architecture, growth direction, and structural sensitivity.

The observations focused on:

- frequency of overfiling;
- client-reported sensitivity;
- thermal discomfort during removal;
- structural condition of the natural nail plate;
- stability of subsequent coatings;
- procedural controllability and ergonomic precision.

The methodological framework of the study is based on the proprietary principles of Zero-Base Safe Removal™, including:

- preservation of the residual protective layer;
- controlled mechanical load distribution;
- vector-guided drill movement;
- ergonomic stabilization;
- free-edge preservation logic;
- thermal control through RPM regulation.

The article does not constitute medical research and does not provide medical diagnosis or treatment recommendations. All presented findings reflect professional preventive observations within the scope of cosmetic nail care practice.

BIOMECHANICS OF THE NAIL PLATE AND MECHANICAL TRAUMA

Structure of the Natural Nail Plate

The natural nail plate is a multilayer keratin structure composed of densely connected keratinized cells. These cells are interconnected through lipid and protein bonds responsible for flexibility, resistance, elasticity, and structural integrity of the nail.

Despite its apparent rigidity, the nail plate has limited resistance to repeated abrasive mechanical stress. The superficial layers of the nail are particularly vulnerable to excessive filing and localized pressure concentration during material removal procedures.

Unlike many biological tissues, the nail plate has limited capacity for immediate structural recovery after mechanical trauma. Repeated disruption of keratin layers may result in:

- chronic thinning;
- increased brittleness;
- loss of elasticity;
- sensitivity during procedures;
- reduced adhesion of future coatings.

Within aggressive removal systems, technicians frequently transition from working on artificial material to direct abrasive interaction with biological keratin tissue. In such conditions, even minor instability in movement trajectory or pressure may lead to irreversible microdamage.

Overfiling as a Mechanical Safety Problem

Overfiling remains one of the most common complications associated with hardware manicure systems. In many cases, overfiling occurs not due to product quality but because of uncontrolled mechanical interaction between the abrasive tool and the natural nail surface.

Factors contributing to overfiling include:

- excessive pressure concentration;
- unstable hand positioning;
- incorrect RPM selection;
- chaotic movement vectors;
- prolonged friction in one area;
- complete removal "to zero."

The consequences of overfiling often extend beyond temporary sensitivity. Clients frequently develop long-term structural weakness, discomfort during future procedures, and increased susceptibility to mechanical stress.

Preventive structural preservation aims to eliminate these risks by introducing controlled mechanical interaction principles into the removal process.

PREVENTIVE STRUCTURAL PRESERVATION CONCEPT

Residual Layer Preservation Principle

One of the central concepts of the Zero-Base Safe Removal™ method is the preservation of a thin residual layer of artificial material during removal procedures.

Within the methodology, this residual layer performs multiple functions:

- protective barrier;
- mechanical damper;
- load distribution element;
- stabilizing surface for future coatings.

The residual layer absorbs part of the friction force generated during drill operation and reduces localized stress concentration on the natural nail plate. From a biomechanical perspective, this transforms the removal process from direct biological abrasion into controlled interaction with artificial material.

Importantly, the methodology does not consider residual material preservation as incomplete work. Instead, the residual layer functions as an intentional preventive component integrated into the technical protocol.



Figure 1. Functional Role of the Residual Protective Layer

Source: Author's proprietary methodology.

The preservation of this controlled residual layer creates a more stable mechanical environment during e-file procedures and supports long-term structural integrity of the natural nail plate.

ERGONOMIC STABILIZATION AND MOVEMENT CONTROL

Importance of Ergonomic Precision

The Zero-Base Safe Removal™ method places significant emphasis on ergonomic stabilization and precision of movement.

According to the methodology, stable hand positioning and controlled finger fixation are not secondary recommendations but mechanical safety requirements.

Without proper stabilization, even technically correct drill speeds cannot ensure procedural safety. Fine motor instability generates micro-vibrations that translate into:

- uneven removal depth;
- irregular movement trajectories;
- localized pressure peaks;
- accidental overfiling.

The method therefore integrates mandatory support positioning for both the technician's working hand and the client's finger.

Vector-Guided Removal System

Another essential preventive principle is the vector-guided movement system.

The methodology requires that drill bit movement follows the natural growth direction of the nail.

This principle:

- preserves structural alignment;
- reduces cross-directional stress;
- improves load distribution;
- minimizes irregular abrasion.

Chaotic or abrupt movement vectors significantly increase the likelihood of:

- grooves;
- point indentations;
- uneven thickness;
- structural imbalance.

By aligning movement with the natural mechanics of the nail, the method creates a more stable and predictable removal process.

THERMAL LOAD REGULATION

Thermal discomfort remains a common complaint among clients undergoing aggressive e-file procedures.

During drill operation, friction generates thermal energy. If pressure concentration or movement instability occurs, localized overheating may develop rapidly.

The Zero-Base Safe Removal™ method integrates thermal control through:

- stable RPM regulation;
- continuous movement;
- pressure reduction;
- avoidance of prolonged friction in one area.

The recommended operational range of approximately 18,000–20,000 RPM provides optimal balance between:

- cutting efficiency;
- rotational stability;
- vibration minimization;
- heat reduction.

Thermal regulation within the methodology is treated as a safety factor directly influencing client comfort and structural preservation.



Figure 2. Preventive Workflow of Structural Preservation

Source: Author's proprietary methodology.

The workflow demonstrates the preventive sequence integrated into the Zero-Base Safe Removal™ methodology.

PROFESSIONAL VALUE AND INDUSTRY SIGNIFICANCE

The professional significance of preventive structural preservation extends beyond technical execution alone.

The Zero-Base Safe Removal™ method contributes to:

- formation of safer procedural standards;
- reduction of mechanical trauma;
- optimization of workflow stability;
- increased predictability of results;
- educational standardization.

An important aspect of the methodology is its scalability. Due to its structured logic and clearly defined technical principles, the system may be integrated into:

- educational programs;
- proprietary training systems;
- instructor certification;
- salon safety protocols;
- professional demonstration formats.

The methodology also reflects a broader transformation within the nail industry — the transition from purely craft-oriented execution toward technologically informed professional practice based on biomechanics, ergonomics, and preventive safety standards.

DISCUSSION

The increasing popularity of hardware manicure systems has significantly expanded both the possibilities and risks associated with modern nail services.

While aggressive removal techniques may temporarily increase procedural speed, they frequently compromise long-term structural preservation and client safety. The growing number of clients presenting with thinning, sensitivity, and structural instability demonstrates the need for safer procedural systems.

Preventive structural preservation methodologies such as Zero-Base Safe Removal™ represent an important shift toward controlled mechanical interaction and responsible professional practice.

The integration of:

- ergonomic stabilization;
- vector-guided movement;
- residual layer preservation;
- thermal control;
- standardized movement systems

creates a reproducible framework for minimizing procedural trauma.

Furthermore, preventive systems contribute not only to safer client outcomes but also to the professionalization of the industry by introducing measurable standards of mechanical safety and technical precision.

CONCLUSION

Preventive structural preservation represents one of the most important directions in the modernization of professional e-file manicure practice.

The Zero-Base Safe Removal™ method introduces a structured preventive system designed to reduce traumatic mechanical interaction during material removal procedures while preserving the integrity of the natural nail plate.

Through integration of:

- residual protective layer preservation;
- controlled pressure distribution;
- ergonomic stabilization;
- vector-guided movement systems;
- thermal load regulation,

the methodology establishes a reproducible professional standard focused on long-term safety, structural preservation, and procedural predictability.

Its educational potential, practical scalability, and biomechanical rationale position the method as a valuable contribution to the development of safer professional standards within the modern nail service industry.

REFERENCES

1. Baran, R., & Dawber, R. (2001). *Diseases of the Nails and their Management*. Blackwell Science.
2. Scher, R. K., & Daniel, C. R. (2005). *Nails: Therapy, Diagnosis, Surgery*. Elsevier Saunders.
3. Piraccini, B. M., & Alessandrini, A. (2015). Nail anatomy and physiology. *Dermatologic Clinics*.
4. Schoon, D. (2017). *Nail Structure and Product Chemistry*. Schoon Scientific.
5. Roberts, D. T. (2010). Nail disorders and their management. *Clinical Dermatology Journal*.
6. ASTM International. (2019). *Standard Guide for Nail Care Products*.
7. European Cosmetology Standards (EQF Framework). (2020).
8. Haneke, E. (2017). Anatomy of the Nail Unit and the Nail Biopsy. *Seminars in Cutaneous Medicine and Surgery*.
9. Rich, P. (2013). Nail Cosmetics and Esthetics. *Dermatologic Therapy*.
10. Lysenok, L. (2026). *Zero-Base Safe Removal™ Methodological Manual*. Proprietary educational material.